



# Scaffolding Bucket

Revolutionize your construction and industrial projects with the Scaffolding Bucket with Yellow Rope by Kasweld. This innovative tool is meticulously crafted to elevate your efficiency, safety, and convenience on scaffolding sites, making it a must-have for professionals who demand the best.

Crafted with precision and engineered for excellence, the Scaffolding Bucket with Yellow Rope is a testament to the fusion of functionality and durability. The heavy-duty polymer material ensures remarkable resilience against impacts, weather fluctuations, and even chemical exposure, making it a reliable companion in diverse working conditions. The vibrant White colour enhances visibility in any environment and showcases your commitment to safety on the job. Picture this – a seamlessly organized workspace, tools and materials within arm's reach, and a swift workflow. The Scaffolding Bucket with Yellow Rope transforms this vision into reality. With a spacious, this bucket accommodates an array of tools, hardware, and materials, eliminating the need for constant trips up and down the scaffold. The 50-foot high-strength polypropylene rope, equipped with a sturdy metal carabiner, ensures easy transportation of the bucket along the scaffold, further streamlining your operations.

## Technical Specification:

Item Name:	Scaffolding Bucket
Brand:	Kasweld
Material:	Heavy-duty, resistant polymer
Size:	12" x 14"
Rope Material:	High-strength, polypropylene
Weight Capacity:	Up to 50 pounds
Bag Color:	White
Rope Color:	Yellow
Features:	Reinforced handle, pour spout
Unit:	Each
Base Color:	Black
Balance:	Sturdy Base
Temperature Resistance:	-20°F to 150°F
Chemical Resistance:	Yes



Batch	Sample QTY	Allowance for rejected product		
1-100	30%	AQL=2.5	AQL=1.0	AQL=0.65
100-200	30%	No of defects ≤ 7	No of defects ≤ 7	0
200-400	30%	No of defects ≤ 7	No of defects ≤ 7	0
500-600	30%	No of defects ≤ 7	No of defects ≤ 7	0
Batch	Product Size	Inspection Tool and method	Sample Qty	Testing result
	Tolerance			Qualified
1-100	±1.0CM	Straight Scale	30%	No of defects ≤ 1
100-200	±1.0CM	Straight Scale	30%	No of defects ≤ 1
200-400	±1.0CM	Straight Scale	30%	No of defects ≤ 1
500-600	±1.0CM	Straight Scale	30%	No of defects ≤ 1

### Safety Precautions:

- Weight Limitation:** Do not exceed the specified load capacity of 50 pounds. Overloading the bucket can compromise the structural integrity and pose a safety hazard.
- Secure Fastening:** Always ensure the metal carabiner is securely attached to the scaffolding structure before placing any tools or materials in the bucket.
- Regular Inspection:** Before each use, thoroughly inspect the bucket, rope, and carabiner for signs of wear, damage, or corrosion. If any issues are detected, discontinue use immediately and replace the damaged components.
- Proper Rope Management:** Avoid kinks, knots, and tangles in the rope, as these can weaken the rope's strength and lead to potential accidents.

### Disclaimer:

The Scaffolding Bucket with Yellow Rope by Kasweld is designed and manufactured to the highest standards to enhance workplace efficiency and safety. However, it is essential to recognize that its use involves inherent risks. By purchasing and using this product, you acknowledge that Kasweld and its affiliates shall not be held liable for any injuries, damages, accidents, or losses that may arise from the use or misuse of this product.

## Our Locations

### China

No.3, Fuan Huayuan,  
Pingdu, Qingdao, China

### USA

17599, Paxton Ave Lansing,  
Illinois 60438 – USA

### India

No.104, 1st Floor, Premier  
Presidency, Langford Road,  
Bengaluru 560025