

# SAFETY PADLOCK

## Product Description

Having a positive quality Safety system, we are involved in presenting a Safety Padlocks. The Safety padlocks with nylon shackle non-conductive and non-spark making it is good for electrical and indoor applications. It is of Nylon Shackle Padlock Oil & Gas, Chemical, Power And Any Industrial & has key system.

Under the direction of our talented team of professionals, we are offering Safety Padlocks which are developed by using qualitative materials and sophisticated techniques with predefined standards of our industry and as per the safety requirement of our customers. This product is widely demanded and acclaimed amongst our customers for their fine finish and Quality Material.

## Technical Specification:

<b>Material :</b>	Shackle Steel
<b>Comes With :</b>	Key System
<b>Usage :</b>	Industrial/Safety
<b>Quality :</b>	Premium
<b>Size Available:</b>	38 MM , 76 MM
<b>Colors:</b>	Available in 8 colors
<b>Shackle Clearence:</b>	1 1/2"
<b>Shackle Diameter:</b>	1/4"
<b>Pulling Strength</b>	4.00KN
<b>Service Temperature:</b>	-20 to 120 C (0 to 250 F)



Hard - Wearing, Standardized.  
Substantial & Identifiable to meet  
compliance.

Excellent erosion & chemical resistance.

Withstand temperature extremes &  
are also UV stable.



### Safety Precautions:

1. Only authorized personnel should have access to the padlock keys.
2. Store keys securely in a designated area to prevent unauthorized access.
3. Regularly inspect the padlock for wear, damage, or malfunction.
4. Operate the padlock with care and avoid unnecessary force to ensure longevity.
5. Follow lockout/tagout procedures in your workplace.
6. Provide training on proper padlock usage to personnel.
7. Adhere to relevant safety regulations and standards.
8. Replace damaged padlocks promptly to maintain effectiveness.

### Use:

1. Secure lockout/tagout procedures during maintenance or servicing.
2. Use for isolating energy sources to prevent accidental startup.
3. Easily identify different padlocks with the variety of available colors.
4. Choose the appropriate size (38 MM or 76 MM) based on application requirements.

## Our Locations

### China

No.3, Fuan Huayuan,  
Pingdu, Qingdao, China

### USA

17599, Paxton Ave Lansing,  
Illinois 60438 – USA

### India

No.104, 1st Floor, Premier  
Presidency, Langford Road,  
Bengaluru 560025